



www.rjc.sa - info@rjc.sa

مؤسسة رمز ركاز الجودة للتجارة Ramz Rikaz Al Joudah Trading Est.

C.R. No: 7055068394

VAT No: 312849650600003

4620 Street No. 10

3602 Al Jazirah Dist.

Riyadh 14262

Saudi Arabia

السجل التجاري: ٧٠٥٥٠٦٨٣٩٤

الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٠٣

٤٦٢٠ شارع رقم ١٠

٣٦٠٢ حي الجزيرة

الرياض ١٤٢٦٢

المملكة العربية السعودية

Datasheet

Dingli JCPT 1912DCL Electric Self-Propelled Scissor Lift

Brand: Dingli



Short Description

Dingli JCPT1912DCL electric self-propelled scissor lift with a maximum working height of 19.00 m, platform height of 17.00 m, and a safe working load of 500 kg. It offers a 3.44 m x 1.17 m platform with a 1.20 m extension deck and is suitable for both indoor and outdoor use.



www.rjc.sa - info@rjc.sa

مؤسسة رمز ركاز الجودة للتجارة Ramz Rikaz Al Joudah Trading Est.

C.R. No: 7055068394

VAT No: 312849650600003

4620 Street No. 10

3602 Al Jazirah Dist.

Riyadh 14262

Saudi Arabia

السجل التجاري: ٧٠٥٥٠٦٨٣٩٤

الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٠٣

٤٦٢٠ شارع رقم ١٠

٣٦٠٢ حي الجزيرة

الرياض ١٤٢٦٢

المملكة العربية السعودية

Full Description

Manufactured by ZHEJIANG DINGLI MACHINERY CO., LTD., the Dingli JCPT1912DCL is a self-propelled scissor lift designed for reliable access in demanding work environments. This electric model combines robust construction with practical features for efficient operation.

The JCPT1912DCL is ideal for a wide range of applications, including indoor and outdoor maintenance, construction, installation, and facility management tasks. Its self-propelled design allows for easy maneuverability on job sites, while the one-way platform extension deck provides additional reach when needed.

Key operational features include proportional joystick controls for precise movement, self-locking gates for safety, and a platform load sense system. The lift is equipped with solid rubber tyres, two-wheel drive, and two-wheel steering, ensuring stable performance on various surfaces. Safety is enhanced with a tilt alarm, motion alarm, emergency stop button, and an onboard fault diagnostic system. The foldable guard rails facilitate transport and storage, and the flashing LED beacon increases visibility on site.

Images





www.rjc.sa - info@rjc.sa

مؤسسة رمز ركاز الجوده للتجارة Ramz Rikaz Al Joudah Trading Est.

C.R. No: 7055068394

VAT No: 312849650600003

4620 Street No. 10

3602 Al Jazirah Dist.

Riyadh 14262

Saudi Arabia

السجل التجاري: ٧٠٥٥٠٦٨٣٩٤

الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٠٣

٤٦٢٠ شارع رقم ١٠

٣٦٠٢ حي الجزيرة

الرياض ١٤٢٦٢

المملكة العربية السعودية

Technical Specifications

Dingli JCPT 1912DCL Electric Self-Propelled Scissor Lift

Specification	Value
Manufacturer	ZHEJIANG DINGLI MACHINERY CO., LTD.
Country of Origin	China
Max. Working Height (Inside)	19.00m
Max. Working Height (Outside)	19.00m
Max. Platform Height (Inside)	17.00m
Max. Platform Height (Outside)	17.00m
Overall Length	3.76m
Overall Width	1.25m
Overall Height (Rails Up)	3.24m
Overall Height (Rails Down)	2.47m
Platform Size (Length×Width)	3.44m×1.17m
Platform Extension Size	1.20m
Ground Clearance (Stowed/Raised)	0.15m/0.025m
Wheelbase	2.89m
Turning Radius (Inside/Outside)	1.00m/3.50m
Tyres	22×9×16
S.W.L	500kg
S.W.L On Extension	500kg
Max. Occupants (Inside/Outside)	2/0
Gradeability	30%
Travel Speed (Stowed)	4.5km/h
Travel Speed (Raised)	0.4km/h
Max. Working Slope	X-1.5°/Y-3°
Up/Down Speed	70/76sec
Overall Weight	7140kg
Hydraulic Tank	50L
Battery	48V/360Ah
Charger	48V/60A
Driving Motor	2×32VAC/3.3kW
Lifting Motor	48VDC/12.0kW
Standard Items	Proportional Joystick Controls; Self-Locking Gates; One-Way Platform Extension Deck; Drivable At Full Height; Solid Rubber Tyres; Two-Wheel Drive; Two-Wheel Steering; Automatic Brake System; Self-Weight Lowering System; Tubing Explosion-Proof System; Onbo