



www.rjc.sa - info@rjc.sa

رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

Datasheet

Rental Genie GS-2632 Electric Scissor Lift

Brand: Genie



Short Description

Rental **Genie GS-2632** Electric Scissor Lift is a compact electric slab scissor lift designed for safe and efficient indoor access work. It offers a maximum indoor working height of **9.96 m**, a platform capacity of **227 kg**, and a slide-out extension deck for improved reach and productivity. With non-marking tires, quiet electric operation, and a narrow chassis, it is ideal for maintenance, installation, and warehouse applications on smooth slab surfaces.



www.rjc.sa - info@rjc.sa

ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah
5207 Al khobar 34622
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

Full Description

Rental Genie GS-2632 Electric Scissor Lift

The Genie GS-2632 Electric Scissor Lift is a compact slab scissor lift designed for safe and efficient elevated access on smooth surfaces. Its electric drive system, narrow machine width, and quiet operation make it a practical choice for indoor work, while its rated indoor and outdoor use adds flexibility for a wide range of jobsite requirements.

Built for productivity in space-restricted areas, the GS-2632 offers stable vertical lifting performance and a practical platform layout that supports maintenance, installation, and fit-out activities. The slide-out extension deck helps operators reach work areas more comfortably without needing to reposition the machine as often.


Key Features

- Compact electric slab scissor lift suitable for tight working areas
- Quiet electric operation with non-marking tires for indoor-friendly use
- Slide-out extension deck for improved working reach
- Driveable at full height for better jobsite efficiency
- Proportional drive and lift controls for smoother operation
- Platform load sense system and pothole protection for added safety
- SmartLink dual zone control system and onboard diagnostics with battery charge indicator

Applications

- Facility maintenance and building services
- Electrical and mechanical installation work
- Warehouse and logistics operations
- Retail fit-out and interior finishing projects
- Ceiling, lighting, ducting, and signage access tasks

Images





www.rjc.sa - info@rjc.sa

ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah
5207 Al khobar 34622
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية
٥٢٠٧ الخبر ٣٤٦٢٢
المملكة العربية السعودية

Technical Specifications

Rental Genie GS-2632 Electric Scissor Lift

Specification	Value
Brand	Genie
Model	GS-2632
Equipment type	Electric Scissor Lift
Working height max - indoor	9.96 m
Working height max - outdoor	7.79 m
Platform height max - indoor	7.96 m
Platform height max - outdoor	5.79 m
Platform height - stowed	1.19 m
Platform length - outside	2.26 m
Platform length - outside extended	3.18 m
Slide-out platform extension deck length	0.91 m
Platform width - outside	0.84 m
Guardrail height	1.10 m
Toeboard height	15 cm
Machine height - stowed (folding rails)	2.31 m
Machine height - stowed (rails lowered)	1.94 m
Machine length - stowed	2.44 m
Machine length - stowed extended	3.33 m
Machine width	0.82 m
Wheelbase	1.85 m
Ground clearance (center) - pothole guards retracted	12 cm
Ground clearance - pothole guards deployed	2.30 cm
Max platform occupancy (indoor/outdoor)	2/1
Lift capacity	227 kg
Lift capacity - extension deck extended	113 kg
Tilt sensor activation (front to back/side to side)	3° / 1.5°
Drive speed - stowed	3.2 km/h
Drive speed - raised	0.8 km/h
Gradeability - stowed	25%
Turning radius - inside/outside	0/2.13 m
Lifting speed - raise/lower	43/33 sec
Tires - solid non-marking	38 × 13 cm



www.rjc.sa - info@rjc.sa

ركز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

Specification	Value
Power - FLA	24V DC (4 × 6V 210Ah)
Power - Lithium-Ion	24V DC (1 × 24V 90Ah)
Hydraulic tank capacity	15 L
Weight	2145 kg
Weight max. (all possible options)	2223 kg
Tire load max.	826 kg
Tire contact pressure	824 kPa
Occupied floor pressure	12.91 kPa
Sound pressure level (ground workstation)	< 70 dBA
Sound pressure level (platform workstation)	< 70 dBA
Vibrations	< 2.5 m/s ²