



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة

## Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٤٠٨٠٨٠٧

VAT NO: 30114388870003

الرقم الضريبي: ٣٣٤٣٨٨٨٧

7279 Al Khobar Al Janubiyah

الخبر جنوبية ٧٢٧٩

5207 Al khobar 34622

الخبر ٣٤٦٣٢٢ ٥٢٧

Saudi Arabia

المملكة العربية السعودية

## Datasheet

### Rental OMMELIFT 2500 E Spider Lift – 25.1m Working Height

Brand: OMMELIFT



#### Short Description

The **OMMELIFT 2500 E** is a compact **trailer-mounted telescopic lift** available for rental, offering up to **25.1 m working height** and strong outreach for maintenance, installation, and façade works. Easy to transport and quick to set up, it provides smooth proportional controls, stable hydraulic outriggers, and a practical basket for efficient work at height.



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة

## Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠١٧٥٨٨

الرقم الضريبي: ٣٣٤٣٨٨٨٧

٧٢٧٩ الخبر جنوبية

٣٤١٣٢٣ الخبر ٥٢٧

المملكة العربية السعودية

### Full Description

The **OMMELIFT 2500 E** is a trailer-mounted access platform designed for safe, efficient work at height across a wide range of job sites. Its trailer format makes transportation simple, while the quick set-up concept helps teams move between locations with minimal downtime.

Built for everyday rental use, the machine focuses on operator confidence and site productivity. Proportional controls support smooth, precise positioning, and the stabilized working setup provides strong footing when working on uneven or variable ground conditions. The platform layout is practical for tools and materials, supporting typical maintenance and installation tasks.

The 2500 E is a strong fit for building maintenance, façade access, lighting and signage works, MEP installation, and general contractors who need flexible access without committing to a dedicated truck-mounted unit. Whether used indoors or outdoors (subject to site conditions), it delivers dependable access performance with straightforward operation and transport convenience.

### Images



Rakaz Al Joudah General Contracting  
www.rjc.sa info@rjc.sa





www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة

## Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٨٠٨٠٨٠

الرقم الضريبي: ٣٣٨٨٨٧١١٤٣

٧٢٧٩ الخبر جنوبية

٣٤٦٣٢٢ الخبر ٥٢٧

المملكة العربية السعودية

## Technical Specifications

### Rental OMMELIFT 2500 E Spider Lift – 25.1m Working Height

Specification	Value
Manufacturer name	OMMELIFT
Model number	2500 E
Equipment type	Trailer lift (telescopic)
Max. working height	25.1 m
Max. platform height	23.1 m
Max. outreach	12.6 m
Max. basket load	200 kg
Basket load at max. outreach (chart)	80 kg
Angle boom length (boom + basket)	2.0 m
Turret rotation	± 355°
Basket rotation	± 41°
Basket size (L x W x H)	1.25 x 0.8 x 1.1 m
Stabilizer pad size	Ø200 mm
Hydraulic stabilizers	Standard
Max. force	17.1 kN
Ground pressure	20.0 kg/cm <sup>2</sup>
Ground pressure with 0.4 x 0.4 m spreader plate	1.1 kg/cm <sup>2</sup>
Outrigger footprint (L x W)	4250 x 4250 mm
Power supply option	230V / 16A
Engine (petrol/diesel)	Optional
Fuel tank capacity	16 l
Generator	24 V / 22 A
Battery pack	24V/200Ah/5h
Charger	24 V / 30 A
Double charger system	Optional
Electric descent	Optional
Hybrid engine rating (if hybrid version)	14 kW / 18.8 hp
Self-propulsion with hydraulic engagement of traction rollers	Standard
Gradeability	14% / 8°



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة

## Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٨٠٨٠٧

VAT NO: 30114388870003

الرقم الضريبي: ٣٠٠١٤٣٨٨٨٧

7279 Al Khobar Al Janubiyah

الخبر جنوبية ٧٢٧٩

5207 Al khobar 34622

الخبر ٣٤٦٢٢ ٥٢٧

Saudi Arabia

المملكة العربية السعودية

Specification	Value
Ground to tire clearance at max. set-up	Min. 170 mm (5.9% / 3.4°)
Total weight (2500 E)	3000 kg
Total weight (2500 EB)	3060 kg
Total weight (2500 EBD)	3180 kg
Controls	Proportional
Flush basket mount	Standard
Electric power outlet in basket	Standard
Tool trays in basket	Standard
Transport length	8410 mm
Transport width	1710 mm
Transport height	2110 mm