



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Datasheet

### Zoomlion ZT26J Telescopic Boom Lift for Rent

Brand: Zoomlion



#### Short Description

**Zoomlion ZT26J** is a diesel telescopic boom lift designed for high-reach outdoor access and demanding job sites. With a working height of up to **28.2 m**, horizontal outreach of **22.5 m**, and a platform capacity of **300 kg (unrestricted)**, it delivers strong performance for steel erection, façade works, MEP installation, and industrial maintenance. Its 4WD drive system, rough-terrain tires, and high gradeability help it work confidently on uneven ground.



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة

## Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

### Full Description

## Zoomlion ZT26J Telescopic Boom Lift (Diesel) – Rental

The Zoomlion ZT26J is a diesel-powered telescopic boom lift built for high-reach access on demanding outdoor job sites. It delivers a maximum working height of **28.20 m**, platform height of **26.20 m**, and horizontal outreach up to **23.31 m**. With dual lift capacity—**300 kg unrestricted** and **454 kg restricted**—it is ideal for construction, steel erection, façade installation, industrial maintenance, and large-scale site work.

### Key Performance

- **Working height:** 28.20 m
- **Platform height:** 26.20 m
- **Horizontal outreach:** 23.31 m
- **Platform capacity (unrestricted / restricted):** 300 kg / 454 kg
- **Turntable swing:** 360° continuous
- **Platform rotation:** ±90°
- **Jib articulation:** 130° (–55° to 75°)
- **Drive speed (stowed):** 5.5 km/h
- **Gradeability:** 45% (24°)
- **Turning radius (inside / outside):** 3.6 m / 6.8 m
- **Max wind speed:** 12.5 m/s

### Rough-Terrain Mobility

Designed for uneven ground, the ZT26J features **4WD** drive mode with front-wheel steering and solid tires, supporting confident maneuvering and positioning on construction sites.

### Dimensions & Weight

- **Stowed length:** 12.50 m
- **Stowed width:** 2.49 m
- **Stowed height:** 2.80 m
- **Platform size (L × W):** 2.44 m × 0.91 m
- **Wheelbase:** 3.05 m
- **Ground clearance:** 0.41 m
- **Gross weight:** 18,900 kg

### Power & Systems

The ZT26J is supplied with diesel engine options (model/region dependent), and includes a **150 L** fuel tank, **150 L** hydraulic tank, and **12V DC** control voltage for jobsite-ready operation.

### Safety & Productivity Features

The ZT26J is engineered for smooth, controlled boom operation and includes integrated monitoring/diagnostics to support reliable uptime. Standard features typically include:

- Proportional controls and horn
- All-motion alarm and flashing beacon
- Self-closing entry gate
- Emergency stop and emergency descent system
- Auto-leveling, tilt protection, and load sensing systems
- On-board diagnostic system with display
- Oscillating axle and swing-out engine tray



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

- AC power to platform and platform work light

## Typical Rental Applications

- Steel structure erection and industrial plants
- Cladding, curtain wall, and façade installation
- MEP works at height (ducting, piping, cable trays)
- Maintenance for warehouses, refineries, and utilities

Note: Specifications and equipment may vary by configuration and market. Confirm required capacity and jobsite conditions (ground bearing, wind limits, access routes) before mobilization.

## Images





www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Technical Specifications

### Zoomlion ZT26J Telescopic Boom Lift for Rent

Specification	Value
Manufacturer	Zoomlion
Country of Origin	China
Model Number	ZT26J
Equipment Type	Telescopic Boom Lift
Standards Compliance	CE; ANSI; CSA
Work Height	28.20 m
Platform Height	26.20 m
Horizontal Outreach	23.31 m
Stowed Length (A)	12.50 m
Stowed Width (B)	2.49 m
Stowed Height (C)	2.80 m
Platform Length (D)	2.44 m
Platform Width (E)	0.91 m
Wheelbase (F)	3.05 m
Tread	2.49 m
Ground Clearance (G)	0.41 m
Platform Capacity (Unrestricted/Restricted)	300 kg / 454 kg
Drive Speed (Stowed)	5.5 km/h
Gradeability	45% (24°)
Turning Radius (Inside)	3.6 m
Turning Radius (Outside)	6.8 m
Turntable Swing	360° continuous
Platform Rotation	±90°
Tail Swing	1.60 m
Jib Articulation Range	130° (-55° to 75°)
Max Wind Speed	12.5 m/s
Engine Options	Cummins QSF2.8 (GB III) 54 kW @ 2400 rpm; Kubota V2607 (EU IV) 55.4 kW @ 2700 rpm; TD 2.9 L4 (EU IIIB/US T4) 50 kW @ 2600 rpm
Fuel Tank Capacity	150 L
Hydraulic Tank Capacity	150 L
Control Voltage	12V DC
Drive Mode	4WD



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

Specification	Value
Steering Mode	Front-wheel
Tires	385/65-24 solid tires
Gross Weight	18900 kg
Standard Features	Horn; Proportional control; All motion alarm; Flashing beacon; Self-closing entry gate; Emergency descent system; Emergency stop button; Auto-leveling system; On-board diagnostic system; Tilt protection system; Oscillating axle; Load sensing system; 4.3 i
Accessories & Options	Platform work light; Anti-collision device; AC power to platform
Highlights	Smooth and stable boom extension control as low as 15 mm/s; Telematic control interface with self-diagnostic monitoring; Work envelope about 10% larger than competitor; Dual lift capacity 300 kg unrestricted and 454 kg restricted